23'3" X 37'4" OASIS



DIMENSIONS

A	18'6¾"	K	6'
B	37'3¾"	L	14'
D	3'4"	M	13'3¾"
E	4'8"	M2	-
F	8'	T	22'1"
G	10'6¾"	S	23'3"
H	4'	N	-
I	4'	P	-
J	4'	U	-

NSPI TYPE	II	AREA	867
PERIMETER	100'9"	CAPACITY	20554



BILL OF MATERIALS

QTY	PART	DESCRIPTION
2	HP106	6' PANEL
1	HP106L	6' PANEL (LIGHT)
2	HP106A	6' PANEL (A/G)
2	HP183S	2'6" SPECIAL PANEL
1	HP102	2' PANEL
3	HP101	1' PANEL
7	HP159	9'R PANEL
1	HP125	(9'R) 3' ROMAN INSERT
1	HP110	(9'R) 2' OVAL INSERT
5	HP119M	9'R REVERSE
1	HP154	4'R PANEL
4	HP121	30° LAZY-ELL PANEL
2	HP113	45° WEDGE
6	HP126	5° WEDGE
30	HP199	BRACE

PANEL SHELF DETAIL



LAYOUT DIMENSIONS

A-B	43'3¾"
A-C	52'3"
B-C	29'3"

A-1	20'7½"	C-3	23'6¾"
A-2	16'2¼"	C-4	18'5¾"
B-3	17'10¼"	C-5	16'5¾"
B-4	17'7½"	C-6	19'5½"
B-5	25'5¾"	C-7	22'8¼"
B-6	21'6¼"	D-1	16'2¼"
		D-2	33'5½"

SLOPE & HOPPER LAYOUT

S1-B	16'7½"	S3-H1	10'1¼"
S1-C	30'8"	S3-H2	9'9¼"
S2-B	29'8¾"	S3-H3	6'2½"
S2-C	16'10½"	S4-H1	2'½"
S3-A	25'5"	S4-H2	6'2¼"
S3-D	14'11½"	S4-H3	9'8½"
S4-A	18'1"	H1-H2	4'7½"
S4-D	21'1¾"	H2-H3	6'1"
H1-A	16'3¼"		
H1-D	20'6¾"		
H2-A	15'9¼"		



STEP BOM
-2 6' PANEL
+2 2' PANEL
+1 BRACE
+1 8' STEP

COPING LAYOUT



NO DIVING WARNING

ATTENTION DEALER/BUILDER:
It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed.

'NO DIVING' WARNING LABELS MUST BE INSTALLED IN NO DIVING AREAS ACCORDING NSPI SPECIFICATIONS

DANGER
NO DIVING
SHALLOW WATER
DIVING MAY CAUSE DEATH OR PERMANENT INJURY

* SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT

PRE-CUT PANEL LEGEND

LIGHT AQUAGENIE

GENERAL NOTES

1. These are finished dimensions ready for the liner.
2. Dimensions are from inside pool panels.
3. The water level should be no more than 6" below the coping receptor (hangtab) slot.

EXCAVATION NOTES

1. Rough excavation should be 2" to 3" deeper in each instance.
2. Soil to have minimum bearing capacity of 2000 P.S.F.
3. Locate top of pool at least 6" above surrounding land elevation.
4. See 'Panel Shelf Detail' for excavation around pool.
5. Fill voids under base of panels and tamp well.
6. Backfill with non-expansive material.

ADDITIONAL NOTES

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY.
The dealer or contractor who sells or installs your pool is an independant contractor and is not an agent of the Manufacturer. The construction methods illustrated here are suggestions and apply only to normal ground conditions. There may be additional precautions and/or methods of construction. Proper installation is the responsibility of the dealer/builder/contractor.

HYDRA POOLS
543 South Main Street - Sweetwater, TN 37874

DATE	PANEL LINE	DRAWING TITLE	DRAWING NUMBER
JAN 2006	HYDRA	23'3" X 37'4" OASIS	10910

Document ID: HF5100, Hydra Standard Panel Layout Drawing
Rev Date: 12/6/2005
Rev Level: A

Copyright © 2006 by Hydra Pools.